

Power Adaptors

The following power adaptors can be used with these products: NPort® DE-211/311, NPort® 5100/5200/5400/6150/6250/6450, NPort® W2004, NPort® 2150/2250 Plus, UC-7110/7410/7420, VPort 251



	PWR-12150-CN-S1	PWR-12120-USJP-S2	PWR-12120-DT-S2	PWR-12200-DT-S1	PWR-12042-US-S2	PWR-12042-EU-S1
Input Rating						
I/P	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz
Input Plug						
Plug Type	CN	US/JP	–	–	US	Euro
Output Rating						
O/P	1.5 A @ 12 VDC	1.2 A @ 12 VDC	1.2 A @ 12 VDC	2 A @ 12 VDC	420 mA @ 12 VDC	420 mA @ 12 VDC
Output Plug						
Connector Type	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.5	S-type 5.5/2.1/7.5	S-type 5.5/2.1/7.5	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.0
Outer Diameter	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm
Inner Diameter	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm
Physical Characteristics						
Dimensions	70 x 45 x 54 mm	75 x 34 x 72 mm	80 x 49.5 x 30 mm	110.8 x 51.8 x 32 mm	62 x 29 x 66 mm	62 x 29 x 78 mm
Weight	200 g	130 g	124.5 g	200 g	85 g	90 g
Cord Length	1800 ± 200 mm	1830 to 1950 mm	1830 mm (min.)	1800 ± 200 mm	1830 ± 150 mm	1830 ± 150 mm
Environmental Limits						
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
Regulatory Approvals						
Safety	UL/PSE	UL/PSE	UL/CE/FCC/TÜV/PSE/SAA	UL/CE/FCC/GS/CCC	UL/FCC	CE/TÜV



	PWR-12042-UK-S1	PWR-12040-AU-S1	PWR-12120-AU-S2	PWR-12150-EU-S2	PWR-12150-UK-S2	PWR-12200-DT-S2
Input Rating						
I/P	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz
Input Plug						
Plug Type	Euro	AU	AU	Euro	UK	–
Output Rating						
O/P	420 mA @ 12 VDC	400 mA @ 12 VDC	1.2 A @ 12 VDC	1.5 A @ 12 VDC	1.5 A @ 12 VDC	2 A @ 12 VDC
Output Plug						
Connector						

Power Cords

The following power cords can be used with these products: CN2510, CN2600 Series, NPort® 5600 Series, NPort® 6600 Series

PWC-C13US-3B-183



US Plug (110 V)
Thickness: 6.8 mm
Max. Current: 10 A
Length: 1830 mm

PWC-C13EU-2B-183



Euro Plug (250 V)
Thickness: 6.8 mm
Max. Current: 10 A
Length: 1830 mm

PWC-C13UK-3B-183



UK Plug (250 V)
Thickness: 6.8 mm
Max. Current: 5 A
Length: 1830 mm

PWC-C13JP-3B-183



Japan Plug (125 V)
Thickness: 7.0 mm
Max. Current: 7 A
Length: 1830 mm

PWC-C13AU-3B-183



AU Plug (250 V)
Thickness: 6.0 mm
Max. Current: 10 A
Length: 1830 mm

PWC-C13CN-3B-183



CN Plug (250 V)
Thickness: 6.0 mm
Max. Current: 10 A
Length: 1830 mm

